

CTSMT003.2

Mitsubishi, Citroën and Peugeot Steering Wheel Control Interface











Vehicle Application

Mitsubishi ASX (GA0) 2010>
Mitsubishi Lancer (CYO) 2010>
Mitsubishi Outlander (CWOW) 2010 - 2013
Mitsubishi Pajero (V8O) 2013>
Mitsubishi Shogun (V8O) 2013>
Mitsubishi Outlander Sport 2010>
Mitsubishi RVR 2010>

Mitsubishi Mirage 2013>
Mitsubishi L200 2015>
Mitsubishi Triton 2015>
Mitsubishi Space-Star 2015>
Mitsubishi Attrage 2015>
Citroen C4-Aircross (B) 2014>
Peugeot 4008 2014>

Key Features

- Retains Steering Wheel Controls
 - Retains OEM Phone Buttons
 - Retains OEM Aux Input

www.connects2.com



ABOUT THIS PRODUCT

CTSMT003.2

Analogue Steering Wheel Control Interface for Mitsubishi, Citroën and Peugeot vehicles. For Non Amplified Vehicles. RCA Connections For OEM AUX Retention (If Feature Is Available)

Yellow

Black

Red

WIRING COLOUR CODES

Purple Right Rear Speaker + Purple/Black Right Rear Speaker -Green Left Rear Speaker + Green/Black Left Rear Speaker -Grev Right Front Speaker + Grey/Black Right Front Speaker -White Left Front Speaker + White/Black Left Front Speaker -

Permanent 12V Ground Ianition 12V

PRIOR TO INSTALLATION

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure that the correct tools are using during the installation to avoid damage to the vehicle or product. Connects2 can not be held responsible for the installation of this product.

TECHNICAL SUPPORT

Connects2 Ltd. want to provide a fast and suitable resolution to any problems encountered during installation of this product. To get in touch with our dedicated technical support team, please fill in a ticket at support.connects2.com and provide as much information as possible.

FOLLOW US ON SOCIAL MEDIA for all the latest updates



/CONNECTS2
Watch us on
YouTube



/CONNECTS2 Like us on facebook



CONNECTS2LTD Follow us on instagram







FITTING GUIDE

- 1. Remove and disconnect the original head unit.
- 2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.





3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit.

NB: This may be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted. Please see the head unit installation manual for further information on where to connect.

Important: This step must be completed before connecting power to the interface. Failure to so do may result in no steering wheel control function.



4. Connect the 14 way molex connector to the interface





5. Connect the male power/speaker ISO harness to the female power/speaker ISO harness from the aftermarket head unit. For aftermarket head units without an ISO connector, please refer to "Wiring Colour Codes" on Pg. 2.





FITTING GUIDE

- 6. Connect red/white RCA connectors to the rear of the aftermarket stereo to retain OEM aux (if feature is available)
- 7. Connect the female vehicle specific connectors on the harness to the male vehicle connector from the vehicle. Test head unit for correct operation.

STEERING WHEEL CONTROL FUNCTIONALITY

Original Button	Function
Volume +	Volume +
Volume -	Volume -
Track +	Track +
Track -	Track -
Mode	Source
Pick Up	Pick Up
Hang Up	Hang Up

Example Steering Wheel Control Configuration

(Actual configuration may differ depending on vehicle model)



