

TS-R1750S/XIEL5 THF5542-B/VI

● PIONEER CORPORATION 2013 1-1, Shin-Okubo, Bunkyo-ku, Kawasaki-shi, Kanagawa 212-0031, JAPAN/MADE IN VIETNAM FABRIKATO IN VIETNAM FABRIKAZO EN VIETNAM FABRIKAZO EN BELGIË  
 ● PIONEER CORPORATION 2013 1-1, Shin-Okubo, Bunkyo-ku, Kawasaki-shi, Kanagawa 212-0031, JAPAN/MADE IN VIETNAM FABRIKATO IN VIETNAM FABRIKAZO EN VIETNAM FABRIKAZO EN BELGIË  
 ● PIONEER CORPORATION 2013 1-1, Shin-Okubo, Bunkyo-ku, Kawasaki-shi, Kanagawa 212-0031, JAPAN/MADE IN VIETNAM FABRIKATO IN VIETNAM FABRIKAZO EN VIETNAM FABRIKAZO EN BELGIË

**HOW TO INSTALL**  
 1. REMOVE THE SPEAKER FROM THE ORIGINAL POSITION.  
 2. REMOVE THE ORIGINAL SPEAKER FROM THE ORIGINAL POSITION.  
 3. REMOVE THE ORIGINAL SPEAKER FROM THE ORIGINAL POSITION.  
 4. REMOVE THE ORIGINAL SPEAKER FROM THE ORIGINAL POSITION.  
 5. REMOVE THE ORIGINAL SPEAKER FROM THE ORIGINAL POSITION.

**CAUTIONS**  
 1. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 2. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 3. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 4. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 5. DO NOT TOUCH THE SURFACE OF THE SPEAKER.

**TECHNICAL SPECIFICATIONS**  
 Model: TS-R1750S  
 Power: 250W MAX  
 Frequency: 20Hz - 20kHz  
 Impedance: 4Ω  
 Dimensions: 170mm x 170mm x 42mm

TS-R1750S 250W MAX 17cm COAXIAL 3-WAY Flush-Mount Car Speaker Haut-Parleurs à Montage Encastré Pour Automobile

**3-Way Speaker**  
 • MAX. MUSIC POWER 250 W  
 • NOMINAL POWER 40 W  
 • WOOFER Ø170 mm  
 • MIDRANGE Ø42 mm CONE  
 • TWEETER Ø15 mm PIEZOELECTRIC  
 • IMPEDANCE 4 OHMS  
 • SENSITIVITY 90 dB (±1.5 dB)  
 • FREQUENCY RESPONSE 36 Hz TO 31 kHz (-20 dB)  
 • GROSS WEIGHT 1.57 kg

**TECHNICAL SPECIFICATIONS**  
 Model: TS-R1750S  
 Power: 250W MAX  
 Frequency: 20Hz - 20kHz  
 Impedance: 4Ω  
 Dimensions: 170mm x 170mm x 42mm

**Pioneer**  
**250W MAX**  
**3WAY VOICES**  
**17cm**

**TS-R1750S**  
 3-Way Speaker / HP 3 Voies / Diffusore 3 Vie  
 Altvoz 3 Vias / Alto-falante 3 Vias  
 Громкоговоритель 3-Х Полосный

**Pioneer**  
**250W MAX**  
**3WAY VOICES**  
**17cm**

**TS-R1750S**  
 HP 3 Voies  
 • PUISSANCE MUSICALE MAXIMUM 250 W  
 • PUISSANCE NOMINALE 40 W  
 • HP GRAVE Ø170 mm  
 • HP MÉDIUM Ø42 mm CÔNE  
 • HP AIGU Ø15 mm PIEZOELECTRIC  
 • IMPEDANCE 4 OHMS  
 • SENSIBILITE 90 dB (±1.5 dB)  
 • BANDE PASSANTE 36 Hz À 31 kHz (-20 dB)  
 • POIDS BRUT 1,57 kg

**CAUTIONS**  
 1. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 2. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 3. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 4. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 5. DO NOT TOUCH THE SURFACE OF THE SPEAKER.

**ATTENTION**  
 1. NE PAS TOUCHER LA SURFACE DU HAUT-PARLEUR.  
 2. NE PAS TOUCHER LA SURFACE DU HAUT-PARLEUR.  
 3. NE PAS TOUCHER LA SURFACE DU HAUT-PARLEUR.  
 4. NE PAS TOUCHER LA SURFACE DU HAUT-PARLEUR.  
 5. NE PAS TOUCHER LA SURFACE DU HAUT-PARLEUR.

**WICHTIG**  
 1. NICHT DIE OBERFLÄCHE DES LAUTSPRECHERS ANFASSEN.  
 2. NICHT DIE OBERFLÄCHE DES LAUTSPRECHERS ANFASSEN.  
 3. NICHT DIE OBERFLÄCHE DES LAUTSPRECHERS ANFASSEN.  
 4. NICHT DIE OBERFLÄCHE DES LAUTSPRECHERS ANFASSEN.  
 5. NICHT DIE OBERFLÄCHE DES LAUTSPRECHERS ANFASSEN.

**PRECAUTIONS**  
 1. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 2. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 3. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 4. DO NOT TOUCH THE SURFACE OF THE SPEAKER.  
 5. DO NOT TOUCH THE SURFACE OF THE SPEAKER.

**Pioneer**  
**250W MAX**  
**3WAY VOICES**  
**17cm**

**TS-R1750S**  
 3-Way Speaker / HP 3 Voies / Diffusore 3 Vie  
 Altvoz 3 Vias / Alto-falante 3 Vias  
 Громкоговоритель 3-Х Полосный

**TECHNICAL DRAWING**  
 Dimensions: 170mm x 170mm x 42mm  
 Mounting holes: 4mm x 20mm (x8)  
 Spacers: 30mm (x2)

**INCLUDED PARTS**  
 • SCREWS (x8)  
 • WASHERS (x8)  
 • BRACKET (x1)  
 • SPEAKER (x2)

**TS-R1750S**  
 HP 3 Voies  
**Pioneer**

**250W MAX**  
**3WAY VOICES**  
**17cm**

**17cm**  
**3WAY VOICES**  
**250W MAX**

**Pioneer**  
**250W MAX**  
**3WAY VOICES**  
**17cm**

**TS-R1750S**  
 HP 3 Voies  
**Pioneer**

**TS-R1750S**  
 HP 3 Voies  
 • PUISSANCE MUSICALE MAXIMUM 250 W  
 • PUISSANCE NOMINALE 40 W  
 • HP GRAVE Ø170 mm  
 • HP MÉDIUM Ø42 mm CÔNE  
 • HP AIGU Ø15 mm PIEZOELECTRIC  
 • IMPEDANCE 4 OHMS  
 • SENSIBILITE 90 dB (±1.5 dB)  
 • BANDE PASSANTE 36 Hz À 31 kHz (-20 dB)  
 • POIDS BRUT 1,57 kg